

## EPSON Stylus. Color 1520 Ink Jet Printer

**1440**  
DPI



- **1440 dpi Photo Quality printing**
- **Maximum engine rated print speeds up to 6 PPM monochrome; 5 PPM color (letter size)\***
- **Versatile paper handling from 4" x 4" up to 17" x 22"**
- **Built-in tractor feed & optional banner paper holder with manual cutter**
- **Macintosh® and Windows® compatible**
- **Optional internal Ethernet® and LocalTalk**



### The most versatile wide format, high-performance color printer.

Although meeting the everyday challenges of your business has never been harder, finding a printer responsive to your company's varied needs has never been easier. Whether you demand high quality business proposals, impressive presentations or exceptionally sharp line art for technical drawings, the EPSON Stylus Color 1520 delivers with astonishing 1440 dpi print quality.

Utilizing EPSON's latest Micro Piezo™ print head technology, Quick-Dry™ inks, and AcuPhoto™ halftoning, in addition to paper support up to 17" x 22", the EPSON Stylus Color 1520 provides the most versatile solutions to your everyday projects.

With its ability to handle up to three paper input sources simultaneously, the EPSON Stylus Color 1520 assures your workgroup will make their best impression, without sacrificing productivity. In addition, the EPSON Stylus Color 1520 can optionally support both Ethernet and LocalTalk networks. Just imagine, versatile paper handling, easy, flexible connectivity, and the highest quality output - at maximum engine rated print speeds up to 6 pages per minute in monochrome and up to 5 pages per minute in color.

Backed by EPSON's reputation for reliability, the EPSON Stylus Color 1520 comes with a full two year limited warranty, so you'll enjoy consistent quality and performance without worries. And for service and assistance that is second-to-none, EPSON offers the EPSON Connection, a toll-free support hotline to answer any questions you may have.

The EPSON Stylus Color 1520, an essential and affordable solution for any business environment.

## EPSON Stylus. Color 1520 Printer Specifications

### Product/Accessory Part Numbers

|                                   |         |
|-----------------------------------|---------|
| EPSON Stylus COLOR 1520           | C211001 |
| Black ink cartridge               | S020108 |
| Color ink cartridge               | S020089 |
| EPSON Ink Jet Back Light Film, A2 | S041130 |
| EPSON Ink Jet Canvas Cloth        | S041132 |
| Banner Paper Kit                  | C811011 |
| Photo Quality Banner Paper        | S041102 |
| Ethernet/EtherTalk Interface Card | C823461 |
| Adobe PostScript Level 2          |         |
| EPSON StylusRIP-MAC               | C842271 |
| EPSON StylusRIP-PC                | C842281 |

### Printing Method

4 color (CMYK) drop-on-demand Micro Piezo ink jet technology

### Nozzle Configuration

Monochrome head: 128 nozzles  
Color head: 64 nozzles x 3 (CMY)

### Resolution

1440 x 720 dpi; 720 x 720 dpi; 360 x 360 dpi; 180 x 180 dpi

### Print Speed\* (letter size)

Maximum engine rated print speeds up to 6 PPM monochrome; 5 PPM color

\* Maximum engine rated speed is 6 PPM in economy mode. Actual print speeds vary with system configuration, software application, page complexity and coverage.

### Print Characteristics (available from DOS)

Bitmap LQ fonts:

EPSON Roman, EPSON Sans Serif, EPSON Courier, EPSON Prestige, EPSON Script

Scalable fonts: (8-32pts.):

EPSON Roman, EPSON Sans Serif, EPSON Roman T, EPSON Sans Serif H

Character tables:

14 international character sets;  
1 legal character set

### Sound Level

45 dB(A) (ISO 7779)

### Printer Language

EPSON ESC/P2™, IBM X24E, optional Adobe PostScript Level 2

### Software Driver

Windows 95, Windows 3.1x, Windows NT 3.5.1 & 4.0, Windows for WorkGroups 3.1x, Macintosh system 7.x, AutoCad for DOS, EPSONPlot HPGL 2 emulation

### Dimensions (W x D x H)

26" x 20" x 8" (W x D x H)  
25.5 lb

### Input Buffer

64 Kb

### Interface

Bi-Directional Parallel Interface (IEEE-1284 Level 1 Device)  
Macintosh compatible 8-pin mini-din serial interface (Up to 1.8 Mbps max. transfer rate)

### Print Direction

Bidirectional with logic seeking in text and graphic modes

### Printable Area

Top margin: .12"                      Left margin: .12"  
Right margin: .12"                    Bottom margin: .54"

### Paper Capacity

Input paper tray: 100 sheets/10 envelopes  
Output paper tray: 30 sheets

### Paper Handling

Single sheets: from 4" x 4" to 17" x 22" including letter, legal, B (11" x 17"), Super B (13" x 19"), C (17" x 22")

Thickness: .0025" to .004"

Weight: 17 to 24 lb

Prints: 13.6" x 21.78" on C-Size paper

Types: Plain, bond, EPSON Photo Quality paper, glossy film & paper, adhesive, card stock, transparencies, banners, labels, envelopes, iron-on transfers, canvas cloth, and back light film

Continuous paper: 4"W to 16"W

Thickness: .0026" to .0039"

Envelopes: No. 10, DL, C5

Thickness: .006" to .020"

Weight: 12 to 24 lb

Banner Paper: 8.3" to 17"W

Thickness: .003" to .004"

Labels (single sheets) Letter

Thickness: .0079"

Labels (continuous) 4" to 16"

Thickness: .0079"

### Environmental Characteristics

Temperature: Operating: 50° to 95° F (10° to 35° C)

Storage: -4° to 140° F (-20° to 60° C)

Humidity: Operating: 20 to 80% relative humidity

Storage: 5 to 85% relative humidity  
(no condensation)

### Safety Approvals

Safety Standards: UL1950 with D3, CSA22.2 950 with D3; EMI FCC Part 15 subpart B class B

### Reliability

Print head life: 2000 million dots/nozzle (color and monochrome)

Total print volume: 75,000 pages (A3)

### Electrical Requirements

Rated voltage: 120V AC +/- 10%

Rated frequency: 50 to 60Hz

Rated current: 0.4A

Power consumption: Approx. 21W  
(ISO/IEC 10561 Letter Pattern)

### Ink Cartridge Life

Black ink life: 1000 pages at 5% coverage at 360 dpi (letter size)

Color ink life: 320 pages at 15% coverage at 360 dpi (5% each cyan, magenta, yellow) (letter size)

Shelf life: 2 years from production

### Warranty

Two year limited in the U.S. and Canada

### Support - The EPSON Connection<sup>SM</sup>

Technical Support U.S. & Canada 800-922-8911

Fax-on-Demand/EPSON Sound Advice 800-442-2110

Download Service 800-442-2007

Pre-Sales Support U.S. & Canada 800-463-7766

Internet Website <http://www.epson.com>

- **Up to 1440 x 720 dpi Photo Quality color printing**

Provides Photo Quality color without additional photo kits  
Produces true laser quality black text on any media

- **Fastest print speeds in its class**

Maximum engine rated print speeds up to 6 pages per minute monochrome and 5 pages per minute color\*  
Special print spooling software allows for continuous work while printing

- **Versatile paper handling**

Standard output tray accepts paper from 4" x 4" up to 17" x 22" (actual printable area is 13.6" x 21.78")  
Built-in tractor feed for continuous feed paper  
Optional banner paper kit includes roll paper holder with cutting guide

- **4 color (CYMK) Quick-Dry™ inks**

Photo Quality color and laser quality black text on any media  
Special ink level detection and notification system

- **Parallel and high speed serial connections standard**

Both Microsoft Windows and Apple Macintosh compatible  
Simultaneous AutoSwitching ports

- **Optional internal Ethernet and LocalTalk**

Fully supports EtherTalk, TCP/IP, and Novell networks  
Fully supports all Apple® LocalTalk networks

- **Optional Adobe® PostScript® Level 2 driver with PANTONE® Calibrated™ approved colors**

Fully compatible with all leading graphic software applications

- **Superior customer service**

Two year limited warranty  
Toll free customer support

YOU'VE GOT TO SEE IT IN COLOR.™

### PROFESSIONAL MARKETING SERVICES, INC.

PMB 28, 4802 East Ray Rd., Phoenix, AZ 85044

(480) 940-5400 FAX (480) 940-5488

email: [pmsi@promarketinc.com](mailto:pmsi@promarketinc.com)

website: [www.promarketinc.com](http://www.promarketinc.com)