



DS-260 HD DIGITAL CAMERA

The ruggedized DS-260HD is an ideal digital camera for demanding environments. A protective outer shell improves the resistance to impact damage, a dust proof covering prevents water from damaging the valuable components of this sophisticated camera. Inside lies a professional quality 1.5 million pixel chip digital camera offering a level of image quality suitable for most imaging applications.

KEY FEATURES

- Two resolution choices 1280x1024 for high quality images or 640x480 for applications that don't require large files (i.e. web)
- 3x Optical Zoom, 7.4mm-22mm, equivalent to the 35-105mm range of a 35mm camera
- Built-in 1.8" color LCD monitor (70,000 pixels)
- Three levels of JPEG compression; Fine(4:1), Normal(8:1) and Basic(16:1)
- Uses solid state SmartMedia™ cards up to 32MB
- ISO 100

BENEFITS

- Special gaskets, seals and a ruggedized body makes the DS-260 HD a water-resistant and dust-proof digital camera, able to withstand rough handling.
- High performance RISC Microprocessor delivers a fast 5-second file save to the SmartMedia™ card.
- Digital Gamma Correction system ensures that output retains natural color and smooth gradations of the original image.
- New Auto-Sensing Flash technology automatically adjusts flash output according to the lighting conditions. Adjustable Flash Intensity output can be adjusted to reduce over & under exposure due to fixed flash exposure modes typical of some cameras.
- Fujinon EBC GLASS LENS coatings improve color quality by reducing glare and reflections that de-grade an image. New Lens Design optimized specifically for the camera's CCD

- MACRO Auto Focus allows focusing as close as 10 inches to the subject. Objects as small as a business card can be photographed with clarity and sharpness.
- Manual Exposure Options enable better exposure for difficult picture taking situations.
- Adjustable Flash Intensity output can be adjusted to reduce over & under exposure due to fixed flash exposure modes typical of some cameras.
- Selectable White Balances accommodates a variety of lighting situations; reduces the need for time consuming color-corrections on the computer.
- High quality Black & White capture for applications using laser printers. Ideal for newsletters.
- Large LCD increases ease of viewing in playback modes.
- Video Preview/ Video Out for on-location or in-studio image confirmation with optional monitor.
- JPEG Image Format recognized by most software packages. Eliminates the need for slow proprietary software to open images. Allows multiple images to be opened at the same time. Requires no proprietary software to access images.

KEY APPLICATIONS

Virtually All Imaging Applications:

- Outdoor Photography
- Sports, Camping & Boating Photography
- Construction Sites
- Medical / Scientific
- Architectural
- Insurance



For additional information contact your Fujifilm Digital Products Dealer/Retailer or contact us at: 800-378-FUJI

website: www.fujifilm.com

KEY PRODUCT SPECIFICATIONS

CCD	1/1.7 inch CCD with 1.5 million square pixels			
Storage Media	SmartMedia™ Card (3.3V, 2-32 MB)			
Resolution	1280 x 1024 / 640 x 480			
File Format	JPEG (Exif) with 3 compression levels (1/4, 1/8, 1/16)			
Number of images	MG-4s	MG-8s	MG-16s	MG-32s
Fine (1/4)	5	12	24	48
Normal (1/8)	11	23	47	96
Basic (1/16)	22	46	92	185
White Balance	Macro: 25-90cm Norm: 90cm to infinity			
Focus	Automatic: 25 cm/ 9.8 in. to infinity			
Lens	Fujinon lens, f= 35mm - 105mm on a 35mm camera			
LCD monitor	1.8 inch D-TFD (70,000 pixels) color LCD monitor			
Video Output	NTSC			
Flash	Automatic (Max) / 3.0m (WIDE ANGLE), 2.0m (telephoto)			
Digital Interface	RS-232C/ RS-422			
Power Source	Rechargeable lithium-ion battery or AC power adapter (AC-5V)			
Dimensions	145 x 106.5 x 100mm / 5.7 x 4.2 x 3.9 in.			
Weight	648 g/ 22.9 oz (excluding batteries)			



Special gaskets, seals and a ruggedized body all make the DS-260 HD a water-resistant and dust-proof digital camera, able to withstand rough handling.

DS-260 HD DIGITAL CAMERA KIT INCLUDES:

- DS-260 HD Digital Camera
- SmartMedia™ Card (8MB, 3.3v)
- Rechargeable lithium-ion battery NP-100
- AC power adapter AC-5V
- Video Cable
- Neck Strap
- Silicon lubricant
- Serial Cable for Windows and Macintosh
- Data transfer software
- TWAIN driver for download
- Adobe PhotoDeluxe

OPTIONAL ACCESSORIES

- SmartMedia™ Cards (MG-4S, MG-8S, MG-16S, MG-32S)
- Floppy Disk Adapter FD-A2
- PC Card Adapter PC-AD3
- Image Memory Card Reader SM-R1
- Battery Charger BC-80
- Rechargeable lithium-ion battery NP-100
- Wide Conversion lens WL-260 HD
- GA645 High Power Flash

SYSTEM REQUIREMENTS:

- | | |
|--|--|
| <ul style="list-style-type: none"> (1) IBM PC/AT or compatible computer
CPU of 80486, 66 MHz or Pentium • Windows™ 95/98/NT 4.0 • RAM of 32 MB or more (Windows™ 95/98) • RAM of 64 MB or more (Windows™ NT 4.0) • 180 MB of free hard disk space • CD-ROM drive | <ul style="list-style-type: none"> (2) Macintosh computer • CPU of 68040 or Power PC • System 7.6.0 to 8.5.1 • 80 MB of free hard disk space • CD-ROM drive |
|--|--|