



Product Number: 36-in Models 54-in Models	1050C 1055CM	2000CP 2500CP 2800CP 3000CP 3500CP 3800CP
	C6074A C6075A Not applicable	C4703A C4704A C6005A C4723A C4724A C6004A
Target Market	Large/Enterprise	Mid-Market
Media Sizes: 36-in Models 54-in Models	8.3- to 36-in wide sheets; 24- and 36-in rolls Not applicable	Sheets up to 36-in wide; 24- and 36-in rolls Sheets up to 36-in wide; 24-, 36-, 42-, and 54-in rolls
Print Length, Max: 36-in Models 54-in Models	300 ft Not applicable	150 ft 150 ft
Print Technology	HP Thermal Inkjet	HP Thermal Inkjet
Print Quality, Black Best	1200 dpi	Not applicable
Print Quality, Color Best	600 dpi	600 dpi
Prints Color	Yes	Yes
Print Cartridges	4—black, cyan, magenta, yellow	4—black, cyan, magenta, yellow
Print Cartridge Capacity	175 ml, 350 ml	400 color images per ink system
Ink Types	Dye-based color, pigment-based black	Dye-based imaging, pigment-based UV
Print Languages, Std	1050C: HP-GL/2, HP-GL, HP RTL, CALS G4; 1055CM: HP-GL/2, HP-GL, HP RTL, CALS G4, Adobe PostScript 3	2000CP/3000CP: HP-GL/2, HP RTL, Adobe PostScript 3; 2800CP/3800CP: Adobe PostScript 3
Print Languages, Opt	1050C: Adobe PostScript 3; 1055CM: None	None
Media Types	Paper (bright white, coated, high-gloss, translucent, vellum, tracing), film (clear and matte)	Paper (coated, glossy), film (coated, glossy, backlit imaging), banners with Tyvek, opaque vinyl
Media Handling/ Document Finishing	Dual path for sheet and roll feed, automatic cutter, optional take-up reel	Sheet and roll feed, automatic cutter, take-up reel (optional on 2000CP/2500CP/2800CP)
Memory, Std	1050C: 16 MB; 1055CM: 32 MB	2000CP/3000CP: 8/12 MB; 2500CP/3500CP: 36 MB, 4.3 GB hard disk; 2800CP/3800CP: 8/12 MB, 64 MB RIP
Memory, Max	128 MB	68 MB
Connectivity, Std	IEEE 1284-compliant bidirectional parallel, HP JetDirect 600N internal print server for Ethernet 10/100Base-TX	2000CP/3000CP: IEEE 1284-compliant bidirectional parallel; 2500CP/3500CP: IEEE 1284-compliant bidirectional parallel, HP JetDirect 400N internal print server for Ethernet 10/100Base-TX, 10Base2; 2800CP/3800CP: IEEE 1284-compliant bidirectional parallel, 10/100Base-T
Connectivity, Opt	HP JetDirect 600N print servers for Token Ring, 10Base2, and LocalTalk	HP JetDirect 400N print servers for Token Ring
U.S. Cost Per Sq Ft, Line Drawings	17 cents ¹	Not applicable
U.S. Cost Per Sq Ft, Images	48 cents ¹	Indoor ink and coated paper: 40 cents
Print Speed, Normal Quality	1:20 black, 2:00 color (2 × 3 ft) ²	45 sq ft/hour, 300 dpi
Print Speed, Best Quality	2:15 black, 4:00 color (2 × 3 ft)	2000CP/2500CP/3000CP/3500CP: 18 sq ft/hr, 600 dpi; 2800CP/3800CP: 29 sq ft/hr, 600 dpi
Typefaces	1050C: None; 1055CM: 136 Adobe Type 1	2000CP/3000CP: None; 2500CP/2800CP/3500CP/3800CP: 136 Adobe Type 1
Dimensions (W × D × H): 36-in Models	62 × 27 × 51 in	2000CP/2500CP/3000CP/3500CP: 61 × 29 × 48 in; 2800CP/3800CP: 61 × 29 × 48 in, plus 6 × 11 × 14-in RIP
54-in Models	Not applicable	2000CP/2500CP/3000CP/3500CP: 78 × 26 × 48 in; 2800CP/3800CP: 78 × 26 × 48 in, plus 6 × 11 × 14-in RIP
Weight	178 lb	2000CP/2500CP: 183 lb; 3000CP/3500CP: 220 lb; 2800CP: 195 lb; 3800CP: 232 lb
	¹ Coated paper, Normal mode.	
	² 2 × 3-ft (D/A1-size) prints of 4775a1 AutoCad file on bond paper in Normal print mode.	