


## HP DesignJet Printer Specifications



	430 450C 488CA	750C Plus 755CM
<b>Product Number:</b>	C4713A C4715A C6082A	C4708B Not applicable
<b>24-in Models</b>	C4714A C4716A C6083A	C4709B C3198B
<b>36-in Models</b>		
<b>Target Market</b>	Small	Mid-Market
<b>Media Sizes:</b>	8.3- to 24-in wide sheets; 24-inch rolls optional	8.3- to 24-in wide sheets; 24-in rolls
<b>24-in Models</b>	8.3- to 24-in wide sheets; 24- and 36-inch rolls optional	8.3- to 36-in wide sheets; 24- and 36-in rolls
<b>36-in Models</b>		
<b>Print Length, Max:</b>		50 ft (9 ft PostScript output)
<b>24-in Models</b>	50 ft	50 ft (9 ft PostScript output)
<b>36-in Models</b>	50 ft	
<b>Print Technology</b>	HP Thermal Inkjet	HP Thermal Inkjet
<b>Print Quality, Black Best</b>	600 dpi addressable	600 dpi
<b>Print Quality, Color Best</b>	430: Not applicable; 450C/488CA: 300 dpi	600 dpi addressable line drawings, 300 dpi images
<b>Prints Color</b>	430: No; 450C/488CA: Yes	Yes
<b>Print Cartridges</b>	430: 1—black; 450C/488CA: 4—black, cyan, magenta, yellow	4—black, cyan, magenta, yellow
<b>Print Cartridge Capacity</b>	40 ml	357 color prints <sup>2</sup>
<b>Ink Types</b>	Dye based	Dye based
<b>Print Languages, Std</b>	430/450C: HP-GL/2, HP-GL, HP RTL; 488CA: HP-GL/2, HP-GL, HP RTL, Adobe PostScript 3 via software RIP	750C Plus: HP-GL/2, HP-GL, HP RTL, CALS; 755CM: HP-GL/2, HP-GL, HP RTL, CALS, Adobe PostScript Level 2
<b>Print Languages, Opt</b>	None	750C Plus: Adobe PostScript Level 2; 755CM: None
<b>Media Types</b>	Paper (plain, vellum, coated, glossy), film (vellum, coated, glossy, clear, matte), HP Translucent Bond for black output only	Paper (plain, vellum, coated, glossy), film (vellum, coated, glossy, clear, matte), HP Translucent Bond for black output only
<b>Media Handling/ Document Finishing</b>	430/450C: Sheet feed, optional roll feed, automatic cutter; 488CA: Sheet feed, roll feed, automatic cutter	Sheet and roll feed, automatic cutter
<b>Memory, Std</b>	4 MB	750C Plus: 8 MB; 755CM: 72 MB
<b>Memory, Max</b>	36 MB	72 MB
<b>Connectivity, Std</b>	430/450C: IEEE 1284-compliant bidirectional parallel, RS-232C; 488CA: IEEE 1284-compliant bidirectional parallel, RS-232C, HP JetDirect external print server	IEEE 1284-compliant bidirectional parallel, RS-232C serial, HP JetDirect print server for Ethernet 10/100Base-TX, 10Base2
<b>Connectivity, Opt</b>	HP JetDirect external print servers	HP JetDirect internal print server for Token Ring
<b>U.S. Cost Per Sq Ft, Line Drawings</b>	18 cents <sup>1</sup>	19 cents <sup>1</sup>
<b>U.S. Cost Per Sq Ft, Images</b>	53 cents <sup>1</sup>	65 cents <sup>1</sup>
<b>Print Speed, Normal Quality</b>	Line drawings: <4:00 (2 × 3 ft)	4:27 (2 × 3 ft) <sup>2</sup>
<b>Print Speed, Best Quality</b>	Line drawings: 4:00; images: 18:00 (2 × 3 ft)	Images: 8:00–9:00 (2 × 3 ft)
<b>Typefaces</b>	430/450C: None; 488CA: 136 Adobe Type 1	35 Adobe Type 1
<b>Dimensions (W × D × H):</b>		
<b>24-in Models</b>	41 × 9 × 13 in	42 × 27 × 47 in
<b>36-in Models</b>	52 × 9 × 13 in	54 × 27 × 47 in
<b>Weight</b>	430/450C: 24-in model: 57 lb; 36-in model: 70 lb; 488CA: 24-in model: 62 lb; 36-in model: 75 lb	750C Plus: 24 in: 108 lb; 36 in: 132 lb; 755CM: 132 lb
	<sup>1</sup> Coated paper, Normal mode.	
	<sup>2</sup> 2 × 3-ft (D/A1-size) prints of 4775a1 AutoCAD file on paper in Normal/Final print mode.	